

General Purpose Lamps

Energy Used Nominal Watts	Bulb	Base	Vendor ID NO. DCL 046135 UPC 46135 Item No.	Ordering Abbreviation Except Volts	Volts	Pkg Qty	Description	Class and Fil.	Life Avg. Rated Hours	Light Output Approx. Lumens	GL	ML		
3	S-6	Cand.	16757	3S6/5	120	240	•Clear, Indicator	B, C-7A	3000	10		1%		
			16759	3S6/5	130	240	•Clear, Indicator ⁴⁴	B, C-7A	3000	12		1%		
4	C-7	Cand.	13542	4C7/BL/2PK	120	24	•Clear, Blister Pack	B, C-9	3000	16			2%	
			13549	4C7/BL/4PK	120	48	•Clear, Blister Pack	B, C-9	3000	16			2%	
			13546	4C7/BULK	120	250	•Clear, Bulk	B, C-9	3000	16			2%	
			13557	4C7/PINK/2PK/BL	120	24	•Pink	B, C-7A	3000	—			2%	
			13556	4C7/BLUE/2PK/BL	120	24	•Blue	B, C-7A	3000	—			2%	
6	S-6	Cand.	16927	6S6/CL/12V	12	120	•Clear, Indicator	B, C-2R	1500	47			1%	
			16929	6S6/CL/24V	24	120	•Clear, Indicator	B, C-7A	1500	48			1%	
			16930	6S6/CL/30V	30	120	•Train and Country Home	B, C-7A	1500	46			1%	
			16960	6S6/CL	120	120	•Clear, Indicator	B, C-7A	1500	41			1%	
			16938	6S6/CL	130	120	•Clear, Indicator	B, C-7A	1500	37			1%	
			16942	6S6/CL/145V	145	120	•Clear, Indicator	B, C-7A	1500	33			1%	
			16943	6S6/CL/155V	155	120	•Clear, Indicator	B, C-7A	1500	36			1%	
			16946	6S6/CL/3	125-130	120	•Clear, Signal ^{8,20}	B, C-7A	5000+	23			1%	
			D.C. Bay	16764	6S6DC/30V	30	120	Clear	B, C-7A	1500	46			1 ¹ / ₆
			16782	6S6DC	120	120	Clear, Indicator	B, C-9	1500	41			1 ¹ / ₆	
			16784	6S6DC	130	120	Clear, Indicator	B, C-9	1500	37			1 ¹ / ₆	
			16790	6S6DC/145V	145	120	Clear, Indicator	B, C-9	1500	37			1 ¹ / ₆	
			7	C-7	Cand.	13608	7C7	120	120	•Clear	B, C-9	3000	43	
13543	7C7/BL/2PK	120				24	•Clear, Blister Pack	B, C-9	3000	43			2%	
WE SUGGEST 4C7/BL/2PK 120 Volts, An Energy Saving Product														
13545	7C7/BL/4PK	120				48	•Clear, Blister Pack	B, C-9	3000	43			2%	
WE SUGGEST 4C7/BL/4PK 120 Volts, An Energy Saving Product														
13544	7C7/W/BL/4PK	120				48	•White, Blister Pack	B, C-9	3000	33			2%	
13609	7C7	130				120	•Clear	B, C-9	3000	42			2%	
13623	7C7/W	120				120	•Ceramic White	B, C-9	3000	33			2%	
13540	7C7/W/BL/2PK	120				24	•White, Blister Pack	B, C-9	3000	33			2%	
13626	7C7/R	120				120	•Red Ceramic	B, C-9	3000				2%	
13629	7C7/O	120	120	•Orange Ceramic	B, C-9	3000				2%				
7½	S-11	Med.	19353	7½S	120	120	•Clear	B, C-9	1400	47		1 ¹ / ₆	2¼	
			19355	7½S	130	120	•Clear, Sign and Dec.	B, C-9	1400	45		1 ¹ / ₆	2¼	
			19432	7½S/CO	120	120	•Orange Ceramic	B, C-9	1400				2¼	
			19426	7½S/CB	120	120	•Blue Ceramic	B, C-9	1400				2¼	
			19429	7½S/CG	120	120	•Green Ceramic	B, C-9	1400				2¼	
			19423	7½S/CR	120	120	•Red Ceramic	B, C-9	1400				2¼	
			19420	7½S/CW	120	120	•White Ceramic	B, C-9	1400	32			2¼	
			19433	7½S/CW/BL	120	12	•White, Blister Pack	B, C-9	1400	32			2¼	

ⓔ means this bulb meets Federal minimum efficiency standards.

■ Energy Saving Product/Value Added Product

● New Item

Footnotes/Symbols pages 167-169